

Compact Fans - All Metal



Compact Fans - All Metal



AC Axial

Model	Bearing	Voltage (VAC)	Frequency (Hz)	Current (mA)	Speed (RPM)	Watt (W)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Noise (dBA)
-------	---------	---------------	----------------	--------------	-------------	----------	----------------	---------------------------------------	-------------

120 x 120 x 38 mm - Metal

12A230HBAC-M	Ball	230	50/60	100/90	2700/3100	17/15	95/107	8.4/9.4	42/46
--------------	------	-----	-------	--------	-----------	-------	--------	---------	-------

172 x 150 x 55 mm - Metal

17A230HBAC-M	Ball	230	50/60	250/230	2800/3250	42/42	195/230	14/16	49/53
--------------	------	-----	-------	---------	-----------	-------	---------	-------	-------

225 x 225 x 80 mm - Metal

225A230HBAC-M	Ball	230	50/60	300/325	2500/2800	65/70	530/600	17/14	59/61
---------------	------	-----	-------	---------	-----------	-------	---------	-------	-------

280 x 280 x 80 mm - Metal

280A230HBAC-M	Ball	230	50/60	590/820	2500/2700	119/130	1090/1130	16.5/20	68/70
---------------	------	-----	-------	---------	-----------	---------	-----------	---------	-------

Also available 115VAC & 415VAC

DC Brushless

Model	Bearing*	Voltage (VDC)	Current (mA)	Speed (RPM)	Watt (W)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Noise (dBA)
-------	----------	---------------	--------------	-------------	----------	----------------	---------------------------------------	-------------

225 x 225 x 80 mm - Metal

225A48HBDC - M	Ball	48	1100	2850	52.8	647	25	67
----------------	------	----	------	------	------	-----	----	----

280 x 280 x 80 mm - Metal

280A48HBDC - M	Ball	48	1900	2700	91.2	1130	22	69
----------------	------	----	------	------	------	------	----	----

Specifications subject to change without notice

